

Product information | TECHNICAL DATA SHEET

GESSO PRIMER. Prepares and primes surfaces to be painted.
400 ml, 13 Oz, 370 g.

GENERAL DESCRIPTION

Product developed for preparing, sealing, priming and improving color adhesion to most surfaces

FEATURES

- Fast drying.
- Excellent flexibility.
- Easy to apply and repaint.
- Excellent adherence.
- Does not contain lead.
- High opacity.

APPLICATIONS

Suitable for the preparation of canvas, wood, paper and metal. Do not use for the preparation of plastics or perform a test prior to use.

- Arts & crafts.
- Fine arts.
- DIY

INSTRUCTIONS FOR USE

- Shake well before use, one minute after hearing the sound of mixer.
- Apply over dry and cleaned surfaces. Remove corrosion. Over PP apply first a primer.
- Apply in thin coats to achieve better results, three thin coats are better than one thick coat.
- After use, turn can upside down and depress valve button for several seconds until only gas emerges so as to prevent clogging.
- Invertir el aerosol para purgar la válvula tras el uso, si se atasca el difusor reemplazarlo por uno de nuevo.
- Don't spray on plugged equipments and use it only in well ventilated areas.
- Ask for MSDS.

PHYSICAL PROPERTIES

Binder	Polyurethane (PU) soluble in water
Color:	White
Dry to the touch (ASTM D-1640 ISO 1517):	30'
Completely dry (ASTM D-1640 ISO 1517):	24-48h'
Thickness of dry layer (ASTM D-823 ISO 2808):	20 µ/coat (2coats)
Adherence (ASTM D-3359 ISO 2409):	B
Theoretical yield (pintado en continuo):	2,5 m ²
Solvent:	Water / Alcohol
Product life:	(Well Stored) 5 years
Heat resistance of paint:	120°C
Condition for application:	Minimum T° 8°C
	Surface T° 5-50°C
	Max. humidity 85% R.H.P

*The adhesion tests have been done on steel plate.

CAUTION



APPEARANCE



LABEL



Gesso Primer

CAP SYSTEM



PACKAGING

Nominal capacity 400 ml.
Heat resistance of packaging: <50°C
Propellant: DME

Box (6 units)
205 X 140 X 200 mm.

